



pears.ChatInvite



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Description

Links to chatmessage

Columns

Column	Type	Null	Default	Comment
ChatID	char(20)	NOT NULL		
WhoID	char(20)	NOT NULL		
ChatDate	timestamp	NULL		
LastResponse	timestamp	NULL		

Primary Key

- ChatID, WhoID

Foreign Keys

Constraint	Columns	References	Delete/update action
Chat	ChatID	pears.Chat (ChatID)	NOT NULL; ON DELETE CASCADE

Referenced By

- No incoming foreign keys found.

Indexes

- No indexes found.



Triggers

- No triggers found.

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."ChatInvite"
-- Table comment: Links to chatmessage
-- Statement count: 3

CREATE TABLE "pears"."ChatInvite" (
    "ChatID"                CHAR(20) NOT NULL
    , "WhoID"                CHAR(20) NOT NULL
    , "ChatDate"            TIMESTAMP NULL
    , "LastResponse"        TIMESTAMP NULL
    , PRIMARY KEY ("ChatID" ASC, "WhoID" ASC)
)
GO

COMMENT ON TABLE "pears"."ChatInvite" IS
    'Links to chatmessage'
GO

ALTER TABLE "pears"."ChatInvite"
    ADD NOT NULL FOREIGN KEY "Chat" ("ChatID" ASC)
    REFERENCES "pears"."Chat" ("ChatID")
    ON DELETE CASCADE
GO
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_chatinvite

Last update: **2026/08/07 19:24**

