



pears.ConsentPersonOptionHistory



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Description

History of changes to person consent (GDPR etc) settings

Columns

Column	Type	Null	Default	Comment
ConsentPersonOptionHistoryID	char(20)	NOT NULL		
ConsentTypeID	char(20)	NULL		
ConsentTypeOptionID	char(20)	NULL		
PersonID	char(20)	NULL		
WhoEntered	char(20)	NULL		
WithdrawDate	date	NULL		
EventDateTime	timestamp	NULL	current timestamp	
ConnectionNumber	integer	NULL		

Primary Key

- ConsentPersonOptionHistoryID

Foreign Keys

Constraint	Columns	References	Delete/update action
ConsentType	ConsentTypeID	pears.ConsentType (ConsentTypeID)	
ConsentTypeOption	ConsentTypeOptionID	pears.ConsentTypeOption (ConsentTypeOptionID)	
Person	PersonID	pears.Person (personid)	ON DELETE CASCADE



Referenced By

- No incoming foreign keys found.

Indexes

- No indexes found.

Triggers

- No triggers found.

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."ConsentPersonOptionHistory"
-- Table comment: History of changes to person consent (GDPR etc) settings
-- Statement count: 5

CREATE TABLE "pears"."ConsentPersonOptionHistory" (
  "ConsentPersonOptionHistoryID"  CHAR(20) NOT NULL
, "ConsentTypeID"                  CHAR(20) NULL
, "ConsentTypeOptionID"           CHAR(20) NULL
, "PersonID"                      CHAR(20) NULL
, "WhoEntered"                    CHAR(20) NULL
, "WithdrawDate"                  DATE NULL
, "EventDateTime"                 TIMESTAMP NULL DEFAULT CURRENT
TIMESTAMP
, "ConnectionNumber"              INTEGER NULL
, PRIMARY KEY ("ConsentPersonOptionHistoryID" ASC)
)
GO

COMMENT ON TABLE "pears"."ConsentPersonOptionHistory" IS
  'History of changes to person consent (GDPR etc) settings '
GO

ALTER TABLE "pears"."ConsentPersonOptionHistory"
  ADD FOREIGN KEY "ConsentType" ("ConsentTypeID" ASC)
```



```
REFERENCES "pears"."ConsentType" ("ConsentTypeID")
GO

ALTER TABLE "pears"."ConsentPersonOptionHistory"
  ADD FOREIGN KEY "ConsentTypeOption" ("ConsentTypeOptionID" ASC)
  REFERENCES "pears"."ConsentTypeOption" ("ConsentTypeOptionID")
GO

ALTER TABLE "pears"."ConsentPersonOptionHistory"
  ADD FOREIGN KEY "Person" ("PersonID" ASC)
  REFERENCES "pears"."Person" ("personid")
  ON DELETE CASCADE
GO
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_consentpersonoptionhistory

Last update: **2026/08/07 19:24**

