



# pears.EmailStaffNotificationAddress



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

## Description

Used for more than a single instance of the above.

## Columns

| Column       | Type         | Null     | Default | Comment |
|--------------|--------------|----------|---------|---------|
| ID           | char(20)     | NOT NULL |         |         |
| Topic        | char(50)     | NOT NULL |         |         |
| EmailAddress | char(250)    | NOT NULL |         |         |
| DepartmentID | char(2)      | NULL     |         |         |
| DivisionID   | char(20)     | NULL     |         |         |
| Body         | long varchar | NULL     |         |         |

## Primary Key

- ID

## Foreign Keys

| Constraint | Columns      | References                                      | Delete/update action |
|------------|--------------|-------------------------------------------------|----------------------|
| department | DepartmentID | <a href="#">pears.Department (departmentid)</a> | ON DELETE SET NULL   |
| division   | DivisionID   | <a href="#">pears.Division (divisionid)</a>     | ON DELETE SET NULL   |

## Referenced By

- No incoming foreign keys found.

## Indexes



| Name                      | Type  | Columns                                       | Detail |
|---------------------------|-------|-----------------------------------------------|--------|
| EmailStaffNotifRecipTopic | Index | Topic, DepartmentID, DivisionID, EmailAddress |        |

## Triggers

- No triggers found.

## Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."EmailStaffNotificationAddress"
-- Table comment: Used for more than a single instance of the above.
-- Statement count: 5
```

```
CREATE TABLE "pears"."EmailStaffNotificationAddress" (
    "ID" CHAR(20) NOT NULL
    , "Topic" CHAR(50) NOT NULL
    , "EmailAddress" CHAR(250) NOT NULL
    , "DepartmentID" CHAR(2) NULL
    , "DivisionID" CHAR(20) NULL
    , "Body" long VARCHAR NULL
    , PRIMARY KEY ("ID" ASC)
)
GO
```

```
COMMENT ON TABLE "pears"."EmailStaffNotificationAddress" IS
    'Used for more than a single instance of the above.'
GO
```

```
ALTER TABLE "pears"."EmailStaffNotificationAddress"
    ADD FOREIGN KEY "department" ("DepartmentID" ASC)
    REFERENCES "pears"."Department" ("departmentid")
    ON DELETE SET NULL
GO
```

```
ALTER TABLE "pears"."EmailStaffNotificationAddress"
    ADD FOREIGN KEY "division" ("DivisionID" ASC)
    REFERENCES "pears"."Division" ("divisionid")
    ON DELETE SET NULL
GO
```



```
CREATE INDEX "EmailStaffNotifRecipTopic" ON  
"pears"."EmailStaffNotificationAddress"  
  ( "Topic", "DepartmentID", "DivisionID", "EmailAddress" )  
GO
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

[https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears\\_emailstaffnotificationaddress](https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_emailstaffnotificationaddress)

Last update: 2026/08/07 19:24

