



pears.IQacNominal



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Description

Nominal Code definitions and behaviour settings

Columns

Column	Type	Null	Default	Comment
NominalCode	char(12)	NOT NULL		
NominalType	char(1)	NOT NULL	'P'	<P>&L or S
Name	char(50)	NOT NULL		
NominalGroup	char(12)	NOT NULL		Used for P&L/BS report
LedgerRelationship	char(30)	NOT NULL		LedgerControl, AccountControl, AccountOptional, AccountRequired, NoAccount
LedgerID	char(12)	NULL		
AccountCode	char(12)	NULL		

Primary Key

- NominalCode

Foreign Keys

Constraint	Columns	References	Delete/update action
NomLedger	LedgerID	pears.IQacLedger (LedgerID)	
NomAccount	LedgerID, AccountCode	pears.IQacAccount (LedgerID, AccountCode)	

Referenced By

Table	Constraint	Columns	Referenced columns
pears.IQacDocumentTemplate	IQacNominal	VATNominalCode	NominalCode



Table	Constraint	Columns	Referenced columns
pears.IQacJournal	IQacNominal	NominalCode	NominalCode
pears.IQacParams	IQacNominal	ReserveNominalCode	NominalCode

Indexes

Name	Type	Columns	Detail
IQacNom_Name	Unique index	Name	

Triggers

- No triggers found.

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."IQacNominal"
-- Table comment: Nominal Code definitions and behaviour settings
-- Statement count: 8
```

```
CREATE TABLE "pears"."IQacNominal" (
  "NominalCode"          CHAR(12) NOT NULL
, "NominalType"          CHAR(1) NOT NULL DEFAULT 'P'
, "Name"                 CHAR(50) NOT NULL
, "NominalGroup"         CHAR(12) NOT NULL
, "LedgerRelationship"   CHAR(30) NOT NULL
, "LedgerID"             CHAR(12) NULL
, "AccountCode"          CHAR(12) NULL
, PRIMARY KEY ("NominalCode" ASC)
)
GO
```

```
COMMENT ON COLUMN "pears"."IQacNominal"."NominalType" IS
  '<P>&L or <B>S'
GO
```

```
COMMENT ON COLUMN "pears"."IQacNominal"."NominalGroup" IS
  'Used for P&L/BS report'
GO
```



```
COMMENT ON COLUMN "pears"."IQacNominal"."LedgerRelationship" IS  
    'LedgerControl, AccountControl, AccountOptional, AccountRequired,  
    NoAccount'  
GO
```

```
COMMENT ON TABLE "pears"."IQacNominal" IS  
    'Nominal Code definitions and behaviour settings'  
GO
```

```
ALTER TABLE "pears"."IQacNominal"  
    ADD FOREIGN KEY "NomLedger" ("LedgerID" ASC)  
    REFERENCES "pears"."IQacLedger" ("LedgerID")  
GO
```

```
ALTER TABLE "pears"."IQacNominal"  
    ADD FOREIGN KEY "NomAccount" ("LedgerID" ASC, "AccountCode" ASC)  
    REFERENCES "pears"."IQacAccount" ("LedgerID", "AccountCode")  
GO
```

```
CREATE UNIQUE INDEX "IQacNom_Name" ON "pears"."IQacNominal"  
    ( "Name" )  
GO
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_iqacnominal

Last update: **2026/08/07 19:24**

