



pears.IQXNetBulletin



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Description

Bulletin/announcement messages shown to candidates or clients in iqxWEB. Bulletins can be time-limited via an expiry date, targeted to candidates, clients, or both, and scoped to specific divisions via "IQXNetBulletinDivision". If no division rows exist for a bulletin it is shown to all divisions. Archived bulletins are hidden without being deleted.

Columns

Column	Type	Null	Default	Comment
IQXNetBulletinID	char(20)	NOT NULL		PK
HTMLBody	long varchar	NULL		Body content of the bulletin (HTML)
WhenCreated	timestamp	NOT NULL	current timestamp	
WhoCreated	char(20)	NOT NULL		
SendToCandidate	tinyint	NULL		1 = visible to candidates
SendToClient	tinyint	NULL		1 = visible to clients
Expiry	date	NULL		Date after which the bulletin no longer shows. NULL = never expires
HTMLTitle	char(250)	NULL		Title of the bulletin (HTML)
Archived	timestamp	NULL		NULL = active; set to a value to archive/hide it

Primary Key

- IQXNetBulletinID

Foreign Keys

Constraint	Columns	References	Delete/update action
Staff	WhoCreated	pears.staff (staffid)	NOT NULL; ON DELETE CASCADE



Referenced By

Table	Constraint	Columns	Referenced columns
pears.IQXNetBulletinDivision	IQXNetBulletin	IQXNetBulletinID	IQXNetBulletinID

Indexes

- No indexes found.

Triggers

- No triggers found.

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."IQXNetBulletin"
-- Table comment: Bulletin/announcement messages shown to candidates or
clients in iqxWEB. Bulletins can be time-limited via an expiry date,
targeted to candidates, clients, or both, and scoped to specific divisions
via "IQXNetBulletinDivision". If no division rows exist for a bulletin it is
shown to all divisions. Archived bulletins are hidden without being deleted.
-- Statement count: 10

CREATE TABLE "pears"."IQXNetBulletin" (
  "IQXNetBulletinID"          CHAR(20) NOT NULL
, "HTMLBody"                  long VARCHAR NULL
, "WhenCreated"               TIMESTAMP NOT NULL DEFAULT CURRENT
TIMESTAMP
, "WhoCreated"                CHAR(20) NOT NULL
, "SendToCandidate"           tinyint NULL
, "SendToClient"              tinyint NULL
, "Expiry"                    DATE NULL
, "HTMLTitle"                 CHAR(250) NULL
, "Archived"                  TIMESTAMP NULL
, PRIMARY KEY ("IQXNetBulletinID" ASC)
)
GO

COMMENT ON COLUMN "pears"."IQXNetBulletin"."IQXNetBulletinID" IS
'PK'
```



GO

```
COMMENT ON COLUMN "pears"."IQXNetBulletin"."HTMLBody" IS  
'Body content of the bulletin (HTML)'
```

GO

```
COMMENT ON COLUMN "pears"."IQXNetBulletin"."SendToCandidate" IS  
'1 = visible to candidates'
```

GO

```
COMMENT ON COLUMN "pears"."IQXNetBulletin"."SendToClient" IS  
'1 = visible to clients'
```

GO

```
COMMENT ON COLUMN "pears"."IQXNetBulletin"."Expiry" IS  
'Date after which the bulletin no longer shows. NULL = never expires'
```

GO

```
COMMENT ON COLUMN "pears"."IQXNetBulletin"."HTMLTitle" IS  
'Title of the bulletin (HTML)'
```

GO

```
COMMENT ON COLUMN "pears"."IQXNetBulletin"."Archived" IS  
'NULL = active; set to a value to archive/hide it'
```

GO

```
COMMENT ON TABLE "pears"."IQXNetBulletin" IS  
'Bulletin/announcement messages shown to candidates or clients in  
iqxWEB. Bulletins can be time-limited via an expiry date, targeted to  
candidates, clients, or both, and scoped to specific divisions via  
"IQXNetBulletinDivision". If no division rows exist for a bulletin it is  
shown to all divisions. Archived bulletins are hidden without being  
deleted.'
```

GO

```
ALTER TABLE "pears"."IQXNetBulletin"  
  ADD NOT NULL FOREIGN KEY "Staff" ("WhoCreated" ASC)  
  REFERENCES "pears"."staff" ("staffid")  
  ON DELETE CASCADE
```



G0

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_iqxnetbulletin

Last update: **2026/08/07 19:24**

