



pears.IQXNetUserClass



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Description

Contains a list of the user classes for IQXWeb

Columns

Column	Type	Null	Default	Comment
IQXNetUserClassID	char(20)	NOT NULL		
Name	char(50)	NOT NULL		
DefaultStaffID	char(20)	NULL		
ReportsFolder	char(250)	NULL		
DatabaseUser	char(50)	NULL		Database actions will be performed with permissions of this user
SelfRegistrationAllowed	tinyint	NULL		
Services	long varchar	NULL		
Calls	long varchar	NULL		
Jobs	long varchar	NULL		
Selects	tinyint	NULL		

Primary Key

- IQXNetUserClassID

Foreign Keys

Constraint	Columns	References	Delete/update action
Staff	DefaultStaffID	pears.staff (staffid)	ON DELETE SET NULL

Referenced By

Table	Constraint	Columns	Referenced columns
pears.globaldocument	IQXNetUserClass	IQXNetUserClassID	IQXNetUserClassID



Table	Constraint	Columns	Referenced columns
pears.IQXNetBehaviourOverride	IQXNetUserClass	IQXNetUserClassID	IQXNetUserClassID
pears.IQXNetLanguageOverride	IQXNetUserClass	IQXNetUserClassID	IQXNetUserClassID
pears.IQXNetReport	IQXNetUserClass	IQXNetUserClassID	IQXNetUserClassID
pears.IQXNetRightAllowed	IQXNetUserClass	IQXNetUserClassID	IQXNetUserClassID
pears.IQXNetRightDefault	IQXNetUserClass	IQXNetUserClassID	IQXNetUserClassID
pears.IQXNetUser	IQXNetUserClass	IQXNetUserClassID	IQXNetUserClassID

Indexes

- No indexes found.

Triggers

- No triggers found.

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."IQXNetUserClass"
-- Table comment: Contains a list of the user classes for IQXWeb
-- Statement count: 4

CREATE TABLE "pears"."IQXNetUserClass" (
  "IQXNetUserClassID"          CHAR(20) NOT NULL
, "Name"                      CHAR(50) NOT NULL
, "DefaultStaffID"            CHAR(20) NULL
, "ReportsFolder"             CHAR(250) NULL
, "DatabaseUser"              CHAR(50) NULL
, "SelfRegistrationAllowed"    tinyint NULL
, "Services"                  long VARCHAR NULL
, "Calls"                    long VARCHAR NULL
, "Jobs"                      long VARCHAR NULL
, "Selects"                   tinyint NULL
, PRIMARY KEY ("IQXNetUserClassID" ASC)
)
GO

COMMENT ON COLUMN "pears"."IQXNetUserClass"."DatabaseUser" IS
  'Database actions will be performed with permissions of this user'
GO
```



```
COMMENT ON TABLE "pears"."IQXNetUserClass" IS  
    'Contains a list of the user classes for IQXWeb'  
GO
```

```
ALTER TABLE "pears"."IQXNetUserClass"  
    ADD FOREIGN KEY "Staff" ("DefaultStaffID" ASC)  
    REFERENCES "pears"."staff" ("staffid")  
    ON DELETE SET NULL  
GO
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_iqxnetuserclass

Last update: **2026/08/07 19:24**

