



pears.IQXNetWizardState



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Description

Tracks where a candidate is in the registration wizard so they can resume mid-flow (e.g. after email validation). A row is created when a candidate begins registration and deleted once registration completes ("NetV2RegistrationComplete"). "WizardID" allows multiple distinct wizard variants (e.g. per division) to run independently; "DEFAULT" is used when no custom wizard is configured.

Columns

Column	Type	Null	Default	Comment
IQXNetUserID	char(20)	NOT NULL		FK to IQXNetUser the registering user
WizardID	char(20)	NOT NULL		Wizard variant identifier DEFAULT or a custom division wizard ID
Path	long varchar	NULL		Current page/step the wizard is on (e.g. EMAILVALIDATION)
PreviousCandState	char(4)	NULL		
WhenCreated	timestamp	NULL	current timestamp	

Primary Key

- IQXNetUserID, WizardID

Foreign Keys

Constraint	Columns	References	Delete/update action
IQXNetUser	IQXNetUserID	pears.IQXNetUser (IQXNetUserID)	NOT NULL; ON DELETE CASCADE

Referenced By

- No incoming foreign keys found.



Indexes

- No indexes found.

Triggers

- No triggers found.

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."IQXNetWizardState"
-- Table comment: Tracks where a candidate is in the registration wizard so
they can resume mid-flow (e.g. after email validation). A row is created
when a candidate begins registration and deleted once registration completes
("NetV2RegistrationComplete"). "WizardID" allows multiple distinct wizard
variants (e.g. per division) to run independently; "DEFAULT" is used when no
custom wizard is configured.
-- Statement count: 6

CREATE TABLE "pears"."IQXNetWizardState" (
    "IQXNetUserID"          CHAR(20) NOT NULL
    , "WizardID"             CHAR(20) NOT NULL
    , "Path"                 long VARCHAR NULL
    , "PreviousCandState"    CHAR(4) NULL
    , "WhenCreated"          TIMESTAMP NULL DEFAULT CURRENT
TIMESTAMP
    , PRIMARY KEY ("IQXNetUserID" ASC, "WizardID" ASC)
)
GO

COMMENT ON COLUMN "pears"."IQXNetWizardState"."IQXNetUserID" IS
    'FK â†’ IQXNetUser â€” the registering user'
GO

COMMENT ON COLUMN "pears"."IQXNetWizardState"."WizardID" IS
    'Wizard variant identifier â€” DEFAULT or a custom division wizard ID'
GO

COMMENT ON COLUMN "pears"."IQXNetWizardState"."Path" IS
```



'Current page/step the wizard is on (e.g. EMAILVALIDATION)'

GO

COMMENT ON TABLE "pears"."IQXNetWizardState" IS

'Tracks where a candidate is in the registration wizard so they can resume mid-flow (e.g. after email validation). A row is created when a candidate begins registration and deleted once registration completes ("NetV2RegistrationComplete"). "WizardID" allows multiple distinct wizard variants (e.g. per division) to run independently; "DEFAULT" is used when no custom wizard is configured.'

GO

ALTER TABLE "pears"."IQXNetWizardState"

ADD NOT NULL FOREIGN KEY "IQXNetUser" ("IQXNetUserID" ASC)

REFERENCES "pears"."IQXNetUser" ("IQXNetUserID")

ON DELETE CASCADE

GO

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_iqxnetwizardstate

Last update: **2026/08/07 19:24**

