



pears.IXSResult



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Description

Used for temporarily storing Index Server search results.

Columns

Column	Type	Null	Default	Comment
IXSQueryID	char(20)	NOT NULL		
RecordID	char(20)	NOT NULL		
Score	integer	NULL		
HitCount	integer	NULL		
Rank	integer	NULL		

Primary Key

- IXSQueryID, RecordID

Foreign Keys

Constraint	Columns	References	Delete/update action
IXSStatus	IXSQueryID	pears.IXSStatus (IXSQueryID)	NOT NULL; ON DELETE CASCADE

Referenced By

- No incoming foreign keys found.

Indexes

Name	Type	Columns	Detail
IXSResultRecID	Unique index	RecordID, IXSQueryID	



Triggers

- No triggers found.

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."IXSResult"
-- Table comment: Used for temporarily storing Index Server search results.
-- Statement count: 4

CREATE TABLE "pears"."IXSResult" (
    "IXSQueryID"          CHAR(20) NOT NULL
  , "RecordID"           CHAR(20) NOT NULL
  , "Score"              INTEGER NULL
  , "HitCount"           INTEGER NULL
  , "Rank"               INTEGER NULL
  , PRIMARY KEY ("IXSQueryID" ASC, "RecordID" ASC)
)
GO

COMMENT ON TABLE "pears"."IXSResult" IS
    'Used for temporarily storing Index Server search results.'
GO

ALTER TABLE "pears"."IXSResult"
    ADD NOT NULL FOREIGN KEY "IXSStatus" ("IXSQueryID" ASC)
    REFERENCES "pears"."IXSStatus" ("IXSQueryID")
    ON DELETE CASCADE
GO

CREATE UNIQUE INDEX "IXSResultRecID" ON "pears"."IXSResult"
    ( "RecordID", "IXSQueryID" )
GO
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_ixsresult



Last update: **2026/08/07 19:24**