



pears.KMLBuffer



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Columns

Column	Type	Null	Default	Comment
ID	char(20)	NOT NULL		
WhenEntered	timestamp	NULL	current timestamp	
KML	long varchar	NULL		

Primary Key

- ID

Foreign Keys

- No outgoing foreign keys found.

Referenced By

- No incoming foreign keys found.

Indexes

Name	Type	Columns	Detail
KMLEntered	Index	WhenEntered	

Triggers

- No triggers found.



Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."KMLBuffer"
-- Table comment:
-- Statement count: 2

CREATE TABLE "pears"."KMLBuffer" (
    "ID" CHAR(20) NOT NULL
    ,"WhenEntered" TIMESTAMP NULL DEFAULT CURRENT
TIMESTAMP
    ,"KML" long VARCHAR NULL
    ,PRIMARY KEY ("ID" ASC)
)
GO

CREATE INDEX "KMLEntered" ON "pears"."KMLBuffer"
( "WhenEntered" )
GO
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_kmlbuffer

Last update: **2026/08/07 19:24**

