



pears.MailServer



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Description

Mail Server configuration

Columns

Column	Type	Null	Default	Comment
MailServerID	char(20)	NOT NULL		
ServerType	char(1)	NOT NULL		S=SMTP I=IMAP
Address	char(200)	NOT NULL		
Port	integer	NULL		
Timeout	integer	NULL		
SSL	smallint	NULL		

Primary Key

- MailServerID

Foreign Keys

- No outgoing foreign keys found.

Referenced By

Table	Constraint	Columns	Referenced columns
pears.agencydetails	IMAPServer	IMAPServer	MailServerID
pears.agencydetails	SMTPServer	SMTPServer	MailServerID

Indexes

- No indexes found.



Triggers

- No triggers found.

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."MailServer"
-- Table comment: Mail Server configuration
-- Statement count: 3

CREATE TABLE "pears"."MailServer" (
    "MailServerID"          CHAR(20) NOT NULL
, "ServerType"             CHAR(1) NOT NULL
, "Address"                CHAR(200) NOT NULL
, "Port"                   INTEGER NULL
, "Timeout"                INTEGER NULL
, "SSL"                    SMALLINT NULL
, PRIMARY KEY ("MailServerID" ASC)
)
GO

COMMENT ON COLUMN "pears"."MailServer"."ServerType" IS
    'S=SMTP I=IMAP'
GO

COMMENT ON TABLE "pears"."MailServer" IS
    'Mail Server configuration'
GO
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_mailserver

Last update: 2026/08/07 19:24

