



pears.ReportDepartment



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Columns

Column	Type	Null	Default	Comment
ReportDepartmentid	char(20)	NOT NULL		
Reportid	char(20)	NULL		
departmentid	char(2)	NULL		

Primary Key

- ReportDepartmentid

Foreign Keys

Constraint	Columns	References	Delete/update action
Report	Reportid	pears.report (reportid)	ON DELETE CASCADE
department	departmentid	pears.Department (departmentid)	ON DELETE CASCADE

Referenced By

- No incoming foreign keys found.

Indexes

Name	Type	Columns	Detail
ReportDepartmentid	Unique index	Reportid, departmentid	

Triggers

- No triggers found.



Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."ReportDepartment"
-- Table comment:
-- Statement count: 4

CREATE TABLE "pears"."ReportDepartment" (
    "ReportDepartmentid" CHAR(20) NOT NULL
    , "Reportid" CHAR(20) NULL
    , "departmentid" CHAR(2) NULL
    , PRIMARY KEY ("ReportDepartmentid" ASC)
)
GO

ALTER TABLE "pears"."ReportDepartment"
    ADD FOREIGN KEY "Report" ("Reportid" ASC)
    REFERENCES "pears"."report" ("reportid")
    ON DELETE CASCADE
GO

ALTER TABLE "pears"."ReportDepartment"
    ADD FOREIGN KEY "department" ("departmentid" ASC)
    REFERENCES "pears"."Department" ("departmentid")
    ON DELETE CASCADE
GO

CREATE UNIQUE INDEX "ReportDepartmentid" ON "pears"."ReportDepartment"
    ( "Reportid", "departmentid" )
GO
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_reportdepartment

Last update: **2026/08/07 19:24**

