



pears.status



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Description

Multi-purpose table holding Person, Vacancy and Progress states.

Columns

Column	Type	Null	Default	Comment
type	char(1)	NOT NULL		
status	char(4)	NOT NULL		
rejectstatus	char(1)	NULL		
isfixed	smallint	NULL		
name	char(40)	NOT NULL		
final	smallint	NULL	0	
help	char(40)	NOT NULL		
sortorder	integer	NULL		
gridsortorder	integer	NULL		
PublishToWeb	smallint	NULL	0	1 to show records with this status on web
AllowSetOnWeb	smallint	NULL	0	1 to allow this status to be set on web
ContactEventClass	char(2)	NULL		
BackgroundColour	integer	NULL	16777215	
FontColour	integer	NULL	0	
IsInterview	smallint	NULL	0	1 for progress interviews
OverrideFormColour	tinyint	NULL	0	

Primary Key

- type, status

Foreign Keys

Constraint	Columns	References	Delete/update action
contactclass	ContactEventClass	pears.contactclass (classcode)	



Referenced By

Table	Constraint	Columns	Referenced columns
pears.PersonStatusDivision	status	Status, Type	status, type
pears.ProgressStatusDivision	status	Status, Type	status, type

Indexes

Name	Type	Columns	Detail
status_sortorder	Index	sortorder	

Triggers

Name	Timing	Event
WPK_status_STATUS	after	insert,delete,update order 1

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."status"
-- Table comment: Multi-purpose table holding Person, Vacancy and Progress
states.
-- Statement count: 9

CREATE TABLE "pears"."status" (
    "type" CHAR(1) NOT NULL
    , "status" CHAR(4) NOT NULL
    , "rejectstatus" CHAR(1) NULL
    , "isfixed" SMALLINT NULL
    , "name" CHAR(40) NOT NULL
    , "final" SMALLINT NULL DEFAULT 0
    , "help" CHAR(40) NOT NULL
    , "sortorder" INTEGER NULL
    , "gridsortorder" INTEGER NULL
    , "PublishToWeb" SMALLINT NULL DEFAULT 0
    , "AllowSetOnWeb" SMALLINT NULL DEFAULT 0
    , "ContactEventClass" CHAR(2) NULL
    , "BackgroundColour" INTEGER NULL DEFAULT 16777215
    , "FontColour" INTEGER NULL DEFAULT 0
    , "IsInterview" SMALLINT NULL DEFAULT 0
    , "OverrideFormColour" tinyint NULL DEFAULT 0
    , PRIMARY KEY ("type" ASC, "status" ASC)
    , CONSTRAINT "StatusLengthCheck" CHECK("length"("Status") <= IF "Type" =
'R' THEN 4 ELSE 1 endif)
```



```
)  
GO  
  
COMMENT ON COLUMN "pears"."status"."PublishToWeb" IS  
    '1 to show records with this status on web'  
GO  
  
COMMENT ON COLUMN "pears"."status"."AllowSetOnWeb" IS  
    '1 to allow this status to be set on web'  
GO  
  
COMMENT ON COLUMN "pears"."status"."IsInterview" IS  
    '1 for progress interviews'  
GO  
  
COMMENT ON TABLE "pears"."status" IS  
    'Multi-purpose table holding Person, Vacancy and Progress states.'  
GO  
  
ALTER TABLE "pears"."status"  
    ADD FOREIGN KEY "contactclass" ("ContactEventClass" ASC)  
    REFERENCES "pears"."contactclass" ("classcode")  
GO  
  
CREATE INDEX "status_sortorder" ON "pears"."status"  
    ( "sortorder" )  
GO  
  
CREATE TRIGGER "WPK_status_STATUS" after INSERT,DELETE,UPDATE ORDER 1 ON  
"pears"."status"  
FOR each statement  
BEGIN  
    CALL "WPKTrackChange"('P', 'STATUS')  
END  
GO  
  
COMMENT TO PRESERVE FORMAT ON TRIGGER "pears"."status"."WPK_status_STATUS"  
IS  
{CREATE TRIGGER WPK_status_STATUS  
after INSERT,DELETE,UPDATE ORDER 1 ON
```



```
STATUS
FOR each statement
BEGIN
    CALL WPKTrackChange('P', 'STATUS')
END
}
GO
```

From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_status

Last update: **2026/08/07 19:24**

