



pears.StatusTag



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Columns

Column	Type	Null	Default	Comment
StatusTagID	char(20)	NOT NULL		
TagID	char(3)	NULL		
TagLocation	char(3)	NULL	'P'	Will always be P but needed for referential integrity
status	char(1)	NULL		

Primary Key

- StatusTagID

Foreign Keys

- No outgoing foreign keys found.

Referenced By

- No incoming foreign keys found.

Indexes

- No indexes found.

Triggers

- No triggers found.



Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."StatusTag"
-- Table comment:
-- Statement count: 2

CREATE TABLE "pears"."StatusTag" (
    "StatusTagID"          CHAR(20) NOT NULL
    , "TagID"               CHAR(3)  NULL
    , "TagLocation"         CHAR(3)  NULL DEFAULT 'P'
    , "status"              CHAR(1)  NULL
    , PRIMARY KEY ("StatusTagID" ASC)
)
GO

COMMENT ON COLUMN "pears"."StatusTag"."TagLocation" IS
    'Will always be P but needed for referential integrity'
GO
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_statustag

Last update: **2026/08/07 19:24**

