



pears.TagCompliance



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Description

Used for tag with expiry dates - set sms/email messages

Columns

Column	Type	Null	Default	Comment
tagComplianceid	char(20)	NOT NULL		
taglocation	char(3)	NULL		
tagid	char(3)	NULL		
SMS	long varchar	NULL		
Email	long varchar	NULL		

Primary Key

- tagComplianceid

Foreign Keys

Constraint	Columns	References	Delete/update action
tag	taglocation, tagid	pears.tag (taglocation, tagid)	ON DELETE CASCADE

Referenced By

- No incoming foreign keys found.

Indexes

Name	Type	Columns	Detail
tagCompliance_id	Index	taglocation, tagid	



Triggers

- No triggers found.

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."TagCompliance"
-- Table comment: Used for tag with expiry dates - set sms/email messages
-- Statement count: 4
```

```
CREATE TABLE "pears"."TagCompliance" (
    "tagComplianceid"          CHAR(20) NOT NULL
    ,"taglocation"              CHAR(3)  NULL
    ,"tagid"                    CHAR(3)  NULL
    ,"SMS"                      long VARCHAR NULL
    ,"Email"                    long VARCHAR NULL
    ,PRIMARY KEY ("tagComplianceid" ASC)
)
GO

COMMENT ON TABLE "pears"."TagCompliance" IS
    'Used for tag with expiry dates - set sms/email messages'
GO

ALTER TABLE "pears"."TagCompliance"
    ADD FOREIGN KEY "tag" ("taglocation" ASC,"tagid" ASC)
    REFERENCES "pears"."tag" ("taglocation","tagid")
    ON DELETE CASCADE
GO

CREATE INDEX "tagCompliance_id" ON "pears"."TagCompliance"
    ( "taglocation","tagid" )
GO
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_tagcompliance



Last update: **2026/08/07 19:24**