



pears.TemplInbox



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Columns

Column	Type	Null	Default	Comment
messageID	char(200)	NULL		
FromName	char(100)	NULL		
ContactName	char(60)	NULL		
Subject	char(100)	NULL		
Received	timestamp	NULL		
AttachmentCount	smallint	NULL		
ContactID	char(21)	NULL		
Attachments	long varchar	NULL		
FromAddress	char(500)	NULL		
LookupCount	smallint	NULL		
TemplInboxID	bigint	NOT NULL	autoincrement	

Primary Key

- TemplInboxID

Foreign Keys

- No outgoing foreign keys found.

Referenced By

- No incoming foreign keys found.

Indexes

- No indexes found.



Triggers

- No triggers found.

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."TempInbox"
-- Table comment:
-- Statement count: 1

CREATE GLOBAL TEMPORARY TABLE "pears"."TempInbox" (
  "messageID"          CHAR(200) NULL
, "FromName"           CHAR(100) NULL
, "ContactName"        CHAR(60)  NULL
, "Subject"            CHAR(100) NULL
, "Received"           TIMESTAMP NULL
, "AttachmentCount"    SMALLINT  NULL
, "ContactID"          CHAR(21)  NULL
, "Attachments"        long VARCHAR NULL
, "FromAddress"         CHAR(500) NULL
, "LookupCount"        SMALLINT  NULL
, "TempInboxID"        BIGINT NOT NULL DEFAULT autoincrement
, PRIMARY KEY ("TempInboxID" ASC)
) ON COMMIT PRESERVE ROWS
GO
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_tempinbox

Last update: 2026/08/07 19:24

