



pears.TempProvTimeSheetHistory



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Description

History for provisional timesheets.

Columns

Column	Type	Null	Default	Comment
TempProvTimeSheetHistoryID	char(20)	NOT NULL		
TempProvTimeSheetID	char(20)	NULL		
TempTimeSheetID	char(20)	NULL		
SerialNumber	char(12)	NULL		
OldStatus	integer	NULL		
NewStatus	integer	NULL		
Description	char(250)	NULL		
StaffID	char(20)	NULL		
WhenEntered	timestamp	NULL	current timestamp	
ExternalUserID	char(40)	NULL		

Primary Key

- TempProvTimeSheetHistoryID

Foreign Keys

Constraint	Columns	References	Delete/update action
TempProvTimeSheet	TempProvTimeSheetID	pears.TempProvTimeSheet (TempProvTimeSheetID)	ON DELETE SET NULL
TempTimesheet	TempTimeSheetID	pears.TempTimeSheet (TempTimeSheetID)	ON DELETE SET NULL
staff	StaffID	pears.staff (staffid)	ON DELETE SET NULL



Referenced By

- No incoming foreign keys found.

Indexes

Name	Type	Columns	Detail
TempProvTimesheetHistory_ExternalUserIDWhenEntered	Index	ExternalUserID, WhenEntered	

Triggers

- No triggers found.

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."TempProvTimeSheetHistory"
-- Table comment: History for provisional timesheets.
-- Statement count: 6

CREATE TABLE "pears"."TempProvTimeSheetHistory" (
  "TempProvTimeSheetHistoryID"    CHAR(20) NOT NULL
, "TempProvTimeSheetID"          CHAR(20) NULL
, "TempTimeSheetID"              CHAR(20) NULL
, "SerialNumber"                  CHAR(12) NULL
, "OldStatus"                     INTEGER NULL
, "NewStatus"                     INTEGER NULL
, "Description"                   CHAR(250) NULL
, "StaffID"                       CHAR(20) NULL
, "WhenEntered"                   TIMESTAMP NULL DEFAULT CURRENT
TIMESTAMP
, "ExternalUserID"                CHAR(40) NULL
, PRIMARY KEY ("TempProvTimeSheetHistoryID" ASC)
)
GO

COMMENT ON TABLE "pears"."TempProvTimeSheetHistory" IS
  'History for provisional timesheets.'
GO
```



```
ALTER TABLE "pears"."TempProvTimeSheetHistory"  
  ADD FOREIGN KEY "TempProvTimeSheet" ("TempProvTimeSheetID" ASC)  
  REFERENCES "pears"."TempProvTimeSheet" ("TempProvTimeSheetID")  
  ON DELETE SET NULL
```

GO

```
ALTER TABLE "pears"."TempProvTimeSheetHistory"  
  ADD FOREIGN KEY "TempTimesheet" ("TempTimeSheetID" ASC)  
  REFERENCES "pears"."TempTimeSheet" ("TempTimeSheetID")  
  ON DELETE SET NULL
```

GO

```
ALTER TABLE "pears"."TempProvTimeSheetHistory"  
  ADD FOREIGN KEY "staff" ("StaffID" ASC)  
  REFERENCES "pears"."staff" ("staffid")  
  ON DELETE SET NULL
```

GO

```
CREATE INDEX "TempProvTimesheetHistory_ExternalUserIDWhenEntered" ON  
"pears"."TempProvTimeSheetHistory"  
  ( "ExternalUserID", "WhenEntered" DESC )
```

GO

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_tempprovtimesheethistory

Last update: **2026/08/07 19:24**

