



pears.TempTimeSheetCancellation



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Description

Holds records of Timesheet Cancellations - works in conjunction with code in the TempTimesheetCancel and TempTimesheetComplete functions.

Columns

Column	Type	Null	Default	Comment
TempTimeSheetCancellationID	char(20)	NOT NULL		
OriginalTempTimesheetID	char(20)	NOT NULL		
PayCorrected	smallint	NOT NULL	0	
ChargeCorrected	smallint	NOT NULL	0	
ReplacementProvTimesheetSerialNumber	char(12)	NULL		Only populated while replacement provisional timesheet exists - blanked afterwards
ContraTempTimeSheetID	char(20)	NULL		
ReplacementTempTimeSheetID	char(20)	NULL		
WhenCancelled	timestamp	NOT NULL	current timestamp	
WhoCancelled	char(20)	NULL		
WhenReplacementCompleted	timestamp	NULL		
WhoCompletedReplacement	char(20)	NULL		
Description	long varchar	NULL		
TimesheetCancelReasonID	char(20)	NULL		

Primary Key

- TempTimeSheetCancellationID



Foreign Keys

Constraint	Columns	References	Delete/update action
TimesheetCancelReason	TimesheetCancelReasonID	pears.TimesheetCancelReason (TimesheetCancelReasonID)	

Referenced By

- No incoming foreign keys found.

Indexes

Name	Type	Columns	Detail
TempTSCanc_Orig	Index	OriginalTempTimesheetID	
TempTSCanc_Contra	Index	ContraTempTimeSheetID	
TempTSCanc_Repl	Index	ReplacementTempTimeSheetID	

Triggers

- No triggers found.

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."TempTimeSheetCancellation"
-- Table comment: Holds records of Timesheet Cancellations - works in
-- conjunction with code in the TempTimesheetCancel and TempTimesheetComplete
-- functions.
-- Statement count: 7

CREATE TABLE "pears"."TempTimeSheetCancellation" (
  "TempTimeSheetCancellationID" CHAR(20) NOT NULL
, "OriginalTempTimesheetID" CHAR(20) NOT NULL
, "PayCorrected" SMALLINT NOT NULL DEFAULT 0
, "ChargeCorrected" SMALLINT NOT NULL DEFAULT 0
, "ReplacementProvTimesheetSerialNumber" CHAR(12) NULL
, "ContraTempTimeSheetID" CHAR(20) NULL
, "ReplacementTempTimeSheetID" CHAR(20) NULL
, "WhenCancelled" TIMESTAMP NOT NULL DEFAULT CURRENT
TIMESTAMP
, "WhoCancelled" CHAR(20) NULL
```



```
, "WhenReplacementCompleted"      TIMESTAMP NULL
, "WhoCompletedReplacement"        CHAR(20) NULL
, "Description"                    long VARCHAR NULL
, "TimesheetCancelReasonID"        CHAR(20) NULL
, PRIMARY KEY ("TempTimeSheetCancellationID" ASC)
)
GO

COMMENT ON COLUMN
"pears"."TempTimeSheetCancellation"."ReplacementProvTimesheetSerialNumber"
IS
    'Only populated while replacement provisional timesheet exists - blanked
    afterwards'
GO

COMMENT ON TABLE "pears"."TempTimeSheetCancellation" IS
    'Holds records of Timesheet Cancellations - works in conjunction with
    code in the TempTimesheetCancel and TempTimesheetComplete functions.'
GO

ALTER TABLE "pears"."TempTimeSheetCancellation"
    ADD FOREIGN KEY "TimesheetCancelReason" ("TimesheetCancelReasonID" ASC)
    REFERENCES "pears"."TimesheetCancelReason" ("TimesheetCancelReasonID")
GO

CREATE INDEX "TempTSCanc_Orig" ON "pears"."TempTimeSheetCancellation"
    ( "OriginalTempTimesheetID" )
GO

CREATE INDEX "TempTSCanc_Contra" ON "pears"."TempTimeSheetCancellation"
    ( "ContraTempTimeSheetID" )
GO

CREATE INDEX "TempTSCanc_Repl" ON "pears"."TempTimeSheetCancellation"
    ( "ReplacementTempTimeSheetID" )
GO
```



From:
<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_temptimesheetcancellation

Last update: **2026/08/07 19:24**

