



pears.Town



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Description

List of Towns used to speed address entry

Columns

Column	Type	Null	Default	Comment
TownID	char(20)	NOT NULL		
Name	char(30)	NOT NULL		
AgencyID	char(20)	NULL		
SortOrder	smallint	NULL		

Primary Key

- TownID

Foreign Keys

Constraint	Columns	References	Delete/update action
AgencyDetails	AgencyID	pears.agencydetails (agencyid)	ON DELETE CASCADE

Referenced By

- No incoming foreign keys found.

Indexes

- No indexes found.



Triggers

Name	Timing	Event
WPK_town_TOWN	after	insert,delete,update order 1

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."Town"
-- Table comment: List of Towns used to speed address entry
-- Statement count: 5

CREATE TABLE "pears"."Town" (
    "TownID" CHAR(20) NOT NULL
    , "Name" CHAR(30) NOT NULL
    , "AgencyID" CHAR(20) NULL
    , "SortOrder" SMALLINT NULL
    , PRIMARY KEY ("TownID" ASC)
)
GO

COMMENT ON TABLE "pears"."Town" IS
    'List of Towns used to speed address entry'
GO

ALTER TABLE "pears"."Town"
    ADD FOREIGN KEY "AgencyDetails" ("AgencyID" ASC)
    REFERENCES "pears"."agencydetails" ("agencyid")
    ON DELETE CASCADE
GO

CREATE TRIGGER "WPK_town_TOWN" after INSERT,DELETE,UPDATE ORDER 1 ON
"pears"."town"
FOR each statement
BEGIN
    CALL "WPKTrackChange"('P','TOWN')
END
GO

COMMENT TO PRESERVE FORMAT ON TRIGGER "pears"."Town"."WPK_town_TOWN" IS
{CREATE TRIGGER WPK_town_TOWN
```



```
after INSERT,DELETE,UPDATE ORDER 1 ON
town
FOR each statement
BEGIN
    CALL WPKTrackChange('P','TOWN')
END
}
GO
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_town

Last update: **2026/08/07 19:24**

