



pears.TrengoMessage



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Columns

Column	Type	Null	Default	Comment
TrengoMessageID	char(20)	NOT NULL		
Ticket	char(20)	NULL		
PersonID	char(20)	NULL		
MessageText	long varchar	NULL		
Created_At	timestamp	NULL		
Messagejson	long varchar	NULL		
Messagestype	char(20)	NULL		
WhenReceived	timestamp	NULL		
ID	char(20)	NULL		

Primary Key

- TrengoMessageID

Foreign Keys

Constraint	Columns	References	Delete/update action
Person	PersonID	pears.Person (personid)	ON DELETE SET NULL

Referenced By

- No incoming foreign keys found.

Indexes

- No indexes found.



Triggers

- No triggers found.

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."TrengoMessage"
-- Table comment:
-- Statement count: 2

CREATE TABLE "pears"."TrengoMessage" (
    "TrengoMessageID"      CHAR(20) NOT NULL
    , "Ticket"              CHAR(20) NULL
    , "PersonID"            CHAR(20) NULL
    , "MessageText"         long VARCHAR NULL
    , "Created_At"          TIMESTAMP NULL
    , "MessageJson"         long VARCHAR NULL
    , "Messagetype"         CHAR(20) NULL
    , "WhenReceived"        TIMESTAMP NULL
    , "ID"                  CHAR(20) NULL
    , PRIMARY KEY ("TrengoMessageID" ASC)
)
GO

ALTER TABLE "pears"."TrengoMessage"
    ADD FOREIGN KEY "Person" ("PersonID" ASC)
    REFERENCES "pears"."Person" ("personid")
    ON DELETE SET NULL
GO
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_trengomessage

Last update: 2026/08/07 19:24

