



pears.WithHoldReason



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Columns

Column	Type	Null	Default	Comment
ReasonID	char(20)	NOT NULL		
Description	char(200)	NULL		
SortOrder	smallint	NULL		
Type	char(1)	NULL		C - Client, A - Agency, T - Candidate

Primary Key

- ReasonID

Foreign Keys

- No outgoing foreign keys found.

Referenced By

Table	Constraint	Columns	Referenced columns
pears.WithHolds	WithHoldReason	ReasonID	ReasonID

Indexes

- No indexes found.

Triggers

- No triggers found.



Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."WithHoldReason"
-- Table comment:
-- Statement count: 2

CREATE TABLE "pears"."WithHoldReason" (
    "ReasonID"                CHAR(20) NOT NULL
    ,"Description"            CHAR(200) NULL
    ,"SortOrder"              SMALLINT NULL
    ,"Type"                   CHAR(1) NULL
    ,PRIMARY KEY ("ReasonID" ASC)
)
GO

COMMENT ON COLUMN "pears"."WithHoldReason"."Type" IS
    'C - Client, A - Agency, T - Candidate'
GO
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_withholdreason

Last update: **2026/08/07 19:24**

