



pears.WPKPickList



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Description

Woodpecker centrally defined (and therefore cached and re-suable) pick lists. Defined either by SQL or choices listed in WPKPickListChoice.

Columns

Column	Type	Null	Default	Comment
WPKPickListID	char(20)	NOT NULL		
Name	char(50)	NOT NULL		
SQLQuery	long varchar	NULL		select description,value from ... If blank uses the WPKPickListChoice items
Notes	long varchar	NULL		
AltWPKTrackerID	char(100)	NULL		Allows subset sql query lists to track changes to the table as a whole (or MULTIPLE tables - use comma sep list) for simplicity of maintenance

Primary Key

- WPKPickListID

Foreign Keys

- No outgoing foreign keys found.

Referenced By

Table	Constraint	Columns	Referenced columns
pears.WPKPickListChoice	WPKPickList	WPKPickListID	WPKPickListID



Indexes

- No indexes found.

Triggers

Name	Timing	Event
WPKPickChange	after	insert,delete,update order 1

Original SQL

```
-- IQX database structure split by table
-- Source: IQXDatabaseStructure - with comments.sql
-- Table: "pears"."WPKPickList"
-- Table comment: Woodpecker centrally defined (and therefore cached and re-
suable) pick lists. Defined either by SQL or choices listed in
WPKPickListChoice.
-- Statement count: 6

CREATE TABLE "pears"."WPKPickList" (
    "WPKPickListID"          CHAR(20) NOT NULL
    , "Name"                  CHAR(50) NOT NULL
    , "SQLQuery"              long VARCHAR NULL
    , "Notes"                 long VARCHAR NULL
    , "AltWPKTrackerID"       CHAR(100) NULL
    , PRIMARY KEY ("WPKPickListID" ASC)
)
GO

COMMENT ON COLUMN "pears"."WPKPickList"."SQLQuery" IS
    'select description,value from ... If blank uses the WPKPickListChoice
items'
GO

COMMENT ON COLUMN "pears"."WPKPickList"."AltWPKTrackerID" IS
    'Allows subset sql query lists to track changes to the table as a whole
(or MULTIPLE tables - use comma sep list) for simplicity of maintenance'
GO

COMMENT ON TABLE "pears"."WPKPickList" IS
    'Woodpecker centrally defined (and therefore cached and re-suable) pick
lists. Defined either by SQL or choices listed in WPKPickListChoice.'
```



GO

```
CREATE TRIGGER "WPKPickChange" after INSERT,DELETE,UPDATE ORDER 1 ON
"pears"."WPKPickList"
REFERENCING NEW AS "lst"
FOR each ROW
BEGIN
    CALL "WPKTrackChange"('P',"lst"."WPKPickListID");
    CALL "WPKTrackChange"('P','*')
END
GO
```

```
COMMENT TO PRESERVE FORMAT ON TRIGGER "pears"."WPKPickList"."WPKPickChange"
IS
{CREATE TRIGGER WPKPickChange
after INSERT,DELETE,UPDATE ORDER 1 ON
WPKPickList
REFERENCING NEW AS lst
FOR each ROW
BEGIN
    CALL WPKTrackChange('P',lst.WPKPickListID);
    CALL WPKTrackChange('P','*')
END
}
GO
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:tables:pears_wpkpicklist

Last update: **2026/08/07 19:24**

