



Install and Configure EWS (Exchange Web Service) Send Mail

1) Firstly you need to have the following SQL Function in your IQX database:

```
ALTER FUNCTION "pears"."EmailProviderDetails"()
RETURNS long VARCHAR
BEGIN
    DECLARE rv long VARCHAR;
    DECLARE crlf CHAR(5);
    SET crlf = "char"(13)+"char"(10);
    -- RETURN null;    -- if not using EWS
    SET rv = 'EWS'+crlf; -- mandatory for EWS
    SET rv = string(rv,(SELECT list(NUMBER,',' ORDER BY pt.name ASC) FROM
Phone AS p KEY JOIN PhoneType AS pt WHERE p.WhoID = UserStaffID AND p.Who =
'U' AND pt.Capabilities = 'E'),crlf); -- one or more sender addresses
separated by ; Use userstaffid to look up valid ones for logged in user.
    -- set rv=rv+'IQXEWSSendMail.exe'+crlf; -- the program to call (with
full path if not either in system path or iqx.exe folder). Notepad.exe handy
for testing.
    SET rv = rv+'IQEWSSendMail.exe'+crlf; -- the program to call (with full
path if not either in system path or iqx.exe folder). Notepad.exe handy for
testing.
    SET rv =
rv+'<ExchangeServerUrl>https://titanic2.iqx.co.uk/EWS/Exchange.asmx</Exchang
eServerUrl>'+crlf; -- All remaining lines are inserted into the
<ServerDetails> block.
    SET rv = rv+'<ExchangeVersion>2010</ExchangeVersion>'+crlf;
    SET rv = rv+'<ExchangeServicePack></ExchangeServicePack>'+crlf;
    RETURN rv
END
```

2) Add the following files to your IQX main program folder.

- 1) IQXEWS.exe
- 2) Microsoft.Exchange.WebServices.dll
- 3) IQXEWS.pfx

Error Reporting

Any error that occurs is written to the *.err file. This file can be found in the same folder as the files above



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

<https://iqxusers.co.uk/iqxhelp/doku.php?id=sa37-00&rev=1420821373>

Last update: **2017/11/16 21:57**

